
datasheet

PLH SLIM

rev. 1.2_01/09/2026

Elegant by design,
being only 4mm in depth, the Slim switch plates lend a touch of refinement to the environment.
Both vertical and horizontal installations are possible, giving greater opportunity for originality in asymmetric layouts.


L.C.4R.0.0

L . 1 . _ 2 . _ _ . _ 3

COLLECTION

ACTUATORS: NUMBERS

0-6	Numbers of push buttons or toggles

INSERTS: NUMBERS

0-6	Numbers of inserts in Country standard

LED: NUMBERS

0-6	Numbers of leds depending the shape

ACTUATORS: TYPE*

C	Round
M	Dash
R	Rectangular
T	Toggle 24V
D	Slider
...	Custom

LED: TYPE

rgbw	RGB+White
...	Custom

SHAPE

C	124×40×4 mm 4,88 × 1,57 in
E	154×40×4 mm 6,06 × 1,57 in
G	190×40×4 mm 7,48 × 1,57 in
A	80 × 80 mm 3,19 × 3,15 in
B	124 × 80 mm 4,88 × 3,15 in
2A	152 × 80 mm 5,98 × 3,15 in
3A	223 × 80 mm 8,78 × 3,15 in
...	Custom

INSERTS (excluded)

LLA	Bticino Living Light Air
KS	Keystone standard
15	ø15mm hole
10	ø10mm hole
5	ø5mm hole
PT	PT1000 hole
NF	_1 ø29/1mm Spot 1W _10 ø29/10mm Spot 1W
eK	ekey dline
...	Custom




* When using toggles indicate the way of orientation. Contact PLH® for different types of toggles.

DESCRIPTION
Keypad in solid metal material (6082 aluminum alloy, brass, stainless steel) machined by CNC machine, from a single sheet, 10mm thickness (8mm + 2mm of shadow gap), in round, square or rectangular format for low voltage control devices and standard inserts, for **indoor use only**

ENVIROMENT
Environment specification
→ Ambient Operating Temperature: 0-40 °C (32-104 °F)
→ Relative Humidity: less than 90%, non-condensing


SHAPES OF THE KEYPADS AND WALLBOXES
The keypads are designed to be used for commercial and standard wallboxes following the bottom specifications


1


Code	Shape	Dim.	Single box	Eu standard	Notes
C		124×40×4 mm 4,88 × 1,57 in			Propretary box
E		154×40×4 mm 6,06 × 1,57 in			Propretary box
G		190×40×4 mm 7,48 × 1,57 in			Propretary box
A		81 × 81 mm 3,19 × 3,19 in			Round or square wallboxes with screws 60mm installation opening
B		124 × 81 mm 4,88 × 3,19 in			503E Italian standard or USA 1-GANG JBox
2A		152 × 81 mm 5,98 × 3,19 in			504E Italian standard or 2 round/square wallboxes joined (71 mm installation opening)
3A		223 × 81 mm 8,78 × 3,19 in			506L Italian standard or 3 round/square wallboxes joined (2×71 mm installation opening)


MATERIALS, TREATMENTS, NUANCE

Aluminium (6082 alloy)


G0021 Ⓐ
Tumbled not protected


F0019 Ⓐ
Anodized brushed silver


F0007 Ⓐ
Anodized brushed black


F0001 Ⓐ
Anodized brushed inox


F0090 Ⓐ
Anodized brushed bronze



F0665 Ⓓ
Iron etched protected



F0022 Ⓓ
Sputtering Metal Bronze not protected


F0024 Ⓓ
Sputtering Metal Zinc not protected


F0003 Ⓑ
Painted Matte RAL 9003


F0491 Ⓑ
Painted Cerakote® Black


F0497 Ⓑ
Painted Cerakote® Gun Metal


F0511 Ⓑ
Painted Cerakote® Silver


F0509 Ⓑ
Painted Cerakote® Rose gold


F0503 Ⓑ
Painted Cerakote® Light Gold


F0510 Ⓑ
Painted Cerakote® Dark Grey

Brass


G0063 Ⓒ
Tumbled not protected


F0513 Ⓒ
Brushed protected


F0005 Ⓒ
Polished Chrome


F0574 Ⓒ
Copper brushed protected


F0053 Ⓓ
Brushed bronze light

Stainless Steel 316L (only for PLH Neo)


G0171 Ⓒ
Natural polished


G0104 Ⓒ
Natural brushed


F0112 Ⓓ
Is Pro® Gun Metal Velvet

2

ACTUATORS

Electrical and mechanical specification

C M

→	Push-Button type:	Snap action momentary switch
→	Rated current / Rated voltage:	50mA - 32V DC (*)
→	Electrical life (full load):	300.000 cycles
→	Stroke:	0,50 mm
→	IP degree:	67 (front panel)
→	Terminals:	PicoBlade connectors / plug with wires 26 AWG

T R

→	Push-Button type:	Double Snap action momentary switch
→	Rated current / Rated voltage:	50mA - 32V DC (*)
→	Electrical life (full load):	300.000 cycles
→	Stroke:	0,50 mm
→	IP degree:	67 (front panel)
→	Terminals:	PicoBlade connectors / plug with wires 26 AWG

D

→	Actuator type:	Slider 0-10V
→	Rated current / Resistance:	50mA -10kΩ
→	Electrical life (full load):	15.000 cycles
→	Travel:	30 mm
→	IP degree:	2x
→	Terminals:	SMD Terminal Block | Push-In Cage Clamp

Regulatory Compliance

The PCB included in the PLH keypads has been tested for Electromagnetic compatibility (EMC) in conformity with the essential requirements of the EN61000-6-2 (2016) - EN61000-6-3 (2007) +A1 (2011).
The PLH products are intended as Low Voltage Architectural Control Interface (Decorative wall-mounted control device for Class 2 systems) and are designed for Class 2 low-voltage systems (<24V DC); are assembled using UL Recognized components (switches, LEDs, plastics where applicable); complies with European directives (CE marking, where applicable). Important Notice: PLH products are not UL Listed as a complete assembly.
The normally open push buttons are designed to be installed only by DC safety transformers with maximum 24V and DO NOT directly control the load. Do not connect high-voltage power to low-voltage terminals. Improper wiring can result in personal injury or damage to the control or to other equipment.

Moreover all PLH components must be installed as described in the technical specification on equipment manufactured in compliance with the regulations, according to the latest safety rules, using certified materials and suitable to the characteristics of the environment and pose.
Installation and verification of compliance are not PLH responsibility.

3

LED

Electrical and mechanical specification

→	Feedback led (**):	0,5 ≤ I ≤ 5 mA (***)
→	Positional Led (**) :	10 mA ≤ 30 V (DC)
→	Terminals:	PicoBlade connectors / plug with wires 26 AWG

(*) Inductive load ARE NOT ALLOWED
(**) Multiples led are with the common connected to - (minus polarity) to + on request
(***) without any limitation of the current. Limitation need to be a part of the interface connect to our led

www.plhitalia.com